


KOFLO STATIC MIXER CONSTRUCTED OF SCHEDULE 80 PVC OR CPVC PIPE WITH *___ FIXED LOW PRESSURE LOSS DESIGN MIXING ELEMENTS

150 LB. RAISED FACE VAN STONE PVC FLANGES

SIZE	"A"					"B"	"C"	"D"	"E"	PORT SIZE (FNPT)
	*NUMBER OF ELEMENTS									
	2	3	4	5	6					
1	11	13	15	17	19	4	5/8"	3-1/8"	4"	1/2"
1-1/2"	14	17	20	24	27	4	5/8"	3-7/8"	5"	1/2"
2	17	22	26	30	34	4	3/4"	4-3/4"	5"	3/4"
2-1/2"	21	26	31	36	42	4	3/4"	5-1/2"	6"	3/4"
3	24	31	36	43	49	4	3/4"	6"	7"	3/4"
4	28	37	46	54	63	8	3/4"	7-1/2"	7"	3/4"
6	37	50	63	76	89	8	7/8"	9-1/2"	8"	1"
8	47	64	81	~	~	8	7/8"	11-3/4"	9"	1"
10	59	81	102	~	~	12	1"	14-1/4"	12"	1"
12	68	94	119	~	~	12	1"	17"	12"	1"

NOTE: MIXERS 8" AND LARGER DO NOT USE TEES

NOTE: 2" AND SMALLER MIXERS USE GRAY SCHEDULE 40 PIPE

		Koflo Corporation 309 CARY POINT DR. CARY, IL 60013	
		SCALE: NONE	APPROVED BY: <i>JLF</i>
DATE: 4/29/98	CUSTOMER:		REVISED: 5/22/08
			REVISED: 7/15/10
			REVISED: 3/3/13
MODEL NO: TYPICAL FLANGED SCH 80. PVC OR CPVC LOW PRESSURE LOSS DESIGN MIXER WITH ONE (1) FNPT INJECTION PORT	DRAWING NUMBER:		KD-1010