


SIZE	"A"					"B"	"C"	"D"	"E"	"F"
	*NUMBER OF ELEMENTS									
	2	3	4	5	6					
1/2"	5	6	7	8	10	4	5/8"	2-3/8"	1-1/2"	1/4"
3/4"	6	8	9	11	13	4	5/8"	2-3/4"	1-1/2"	1/4"
1"	7	9	11	13	15	4	5/8"	3-1/8"	2"	1/4"
1-1/2"	11	15	18	21	24	4	5/8"	3-7/8"	2-3/4"	1/2"
2"	13	17	21	26	30	4	3/4"	4-3/4"	2-3/4"	1/2"
2-1/2"	15	20	26	31	37	4	3/4"	5-1/2"	3"	1/2"
3"	19	26	33	40	47	4	3/4"	6"	4"	3/4"
4"	23	33	42	52	61	8	3/4"	7-1/2"	4"	3/4"
6"	33	48	61	74	88	8	7/8"	9-1/2"	4"	3/4"
8"	43	61	79	~~	~~	8	7/8"	11-3/4"	5"	1"
10"	51	74	97	~~	~~	12	1"	14-1/4"	5"	1"
12"	60	88	~~	~~	~~	12	1"	17"	6"	1"

NOTE: SCH 40 IS USED FOR CARBON STEEL MIXERS
SCH 10 IS USED FOR SS/ALLOY MIXERS 3" AND LARGER

		Koflo Corporation 309 CARY POINT DR. CARY, IL 60013	
		SCALE: NONE	APPROVED BY: <i>JLF</i>
DATE: 7/10/06		DRAWN BY: NJF	
CUSTOMER:		REVISED: 5/30/08	
MODEL NO:		REVISED:	
TYPICAL LOW PRESSURE LOSS DESIGN FLANGE MOUNTED MIXER WITH FNPT INJECTION PORT		DRAWING NUMBER: KD-985	